

MQV 10W-40

| | | | | |
|---------|---------|----------|-----------|--------|
| 1 LITRE | 5 LITRE | 25 LITRE | 205 LITRE | BULK |
| VOL105 | VOL115 | VOL155 | VOL215 | VOL705 |

PRODUCT SPECIFICATION

Description

MQV specification semi-synthetic engine oil formulated to deliver strong cold start performance and excellent lubrication at high temperature levels for petrol and diesel engines.

MQV 10W-40 is a semi-synthetic multi-grade engine oil formulated to achieve the performance and efficiency demands of modern petrol and diesel engines requiring low viscosity oils. Advanced additive technology provides long-term benefits including reduced wear on critical valve-train components. Recommended for use in 4-stroke petrol and diesel engines, including turbocharged and supercharged units, fitted in passenger cars and light commercial vehicles, can also be used in ATVs (with dry clutches), horticultural equipment and generators.

- Improved engine efficiency and fuel economy
- Optimised oil pressure at high temperatures
- Improved engine cleanliness

Performance Levels

ACEA A3 / B4

API SN / CF

MB 229.3

Renault RN0700 / 0710

VW 501.00 / 505.00

MQV 10W-40 oil has shown no harm in use with engines requiring Fiat 9.55535-G2 / D2 qualified lubricants.

| Physical Characteristics | |
|--------------------------|-------|
| Viscosity at 100°C, cSt. | 13.7 |
| Viscosity @ 40°C, cSt. | 92.4 |
| Viscosity Index | 150 |
| TBN, mg/KOH/g | 10 |
| Flash Point (Closed), °C | 203 |
| Density at 15.6°C | 0.868 |
| Pour Point, °C | -39 |

Figures based on average production values.

TDS Oil MQV 10W-40 - 21.05.19 Issue 3

