

MQX 5W-40

1 LITRE	5 LITRE	25 LITRE	205 LITRE	BULK
VOL121	VOL120	VOL122	VOL134	VOL700

PRODUCT SPECIFICATION

Description

High performance fully synthetic engine oil formulated for use in vehicles that demand superior lubrication performance and characteristics.

MQX 5W-40 is a fully synthetic engine oil developed directly from motor racing technology to outperform conventional oils in the latest generation of diesel and petrol engines. Designed to cope with the demands of the latest petrol and diesel engine designs, including turbocharged and supercharged units, requiring an oil of this viscosity and specification. may be used against VW 501.01 / 505.01 standards but only for fixed service intervals.

- Improved engine efficiency and fuel economy
- Low volatility levels
- Excellent cold starting characteristics to protect against engine wear and reduce engine noise
- Offers improved flow rates at low temperatures and increased film strength at high temperatures

Performance Levels

ACEA A3 / B4

API SN / CF

Fiat 9.55535-G1, H2, H3, M2, N2*

MB 229.3 / 226.5

Porsche A40

PSA B71 2300

Renault RN0700, RN0710

VW 502.00, 505.00

*May be considered for use where the following specifications are listed: Fiat 9.55535-G1 / H2 / H3 / M2 / N

Physical Characteristics	
Viscosity at 100°C, cSt.	14.2
Viscosity @ 40°C, cSt.	86.2
Viscosity Index	171
TBN, mg/KOH/g	10.1
Flash Point (Closed), °C	203
Density at 15.6°C	0.855
Pour Point, °C	-33

Figures based on average production values.

TDS Oil MQX 5W-40 - 21.05.19 Issue 4

